



Emotional handling

ADVAN FLEVA V701



SPEED RANGE

W/V

- 20 inch
- 19 inch
- 18 inch
- 17 inch
- 16 inch
- 15 inch



Pattern No. V701

Cool & Attractive Design

A direction pattern offers an attractive and aggressive look.

Directional tread pattern

Features a directional tread pattern with more edges facing the road surface. A direction pattern offers an attractive and aggressive look.

Lightning-shaped straight grooves

The main grooves have more edge components through a lightning-shaped design. In addition to the improved traction this delivers excellent hydroplaning resistance.

Wide sword grooves

The lug grooves have more edge components. The non-penetrating lug groove increases block stiffness and enhances the direct feeling of handling.



Claw grooves

The claw grooves push aside water at corners. The groove design increases effective groove length.

Most advanced ADVAN profile

- Profile adapted from the ADVAN Sport V105.
- Improvement of the steering stability by high speed range requested by European car manufacturer.
- Improvement of optimization of the ground contact.



Differentiating between the pitch layout for the shoulder and center

- Increased tread pattern stiffness realizes a more direct feeling to handling.
- Optimized ground contact area.
- Reduces tire noise, and enhances ride quietness.



ADVAN FLEVA V701 Pattern No. V701

| Inch | Series | Dimensions | RF/XL | Overall Diameter (mm) | Approved Rim Width (inch) |
|---------------|----------------|----------------|-------|-----------------------|---------------------------|
| 20 | 30 | 255/30R20 92W | XL | 662 | 8.5-9.5 |
| | | 275/30R20 97W | XL | 674 | 9-10 |
| | | 285/30R20 99W | XL | 681 | 9.5-10.5 |
| | 35 | 225/35R20 90W | XL | 665 | 7.5-9 |
| | | 275/35R20 102W | XL | 702 | 9-11 |
| 19 | 30 | 245/40R20 99W | XL | 704 | 8-9.5 |
| | | 255/30R19 91W | XL | 637 | 8.5-9.5 |
| | | 265/30R19 93W | XL | 642 | 9-10 |
| | 35 | 225/35R19 88W | XL | 642 | 7.5-9 |
| | | 235/35R19 91W | XL | 648 | 8-9.5 |
| 40 | 245/35R19 93W | XL | 655 | 8-9.5 | |
| | | 255/35R19 96W | XL | 661 | 8.5-10 |
| | 275/35R19 100W | XL | 673 | 9-11 | |
| | | 225/40R19 93W | XL | 665 | 7.5-9 |
| | 245/40R19 98W | XL | 680 | 8-9.5 | |
| | | 275/40R19 105W | XL | 704 | 9-11 |
| | 45 | 225/45R19 92W | | 686 | 7-8.5 |
| | | 225/45R19 96W | XL | 687 | 7-8.5 |
| | 235/45R19 95W | | 695 | 7.5-9 | |
| | | 18 | 35 | 215/35R18 84W | XL |
| 225/35R18 87W | XL | | | 614 | 7.5-9 |
| 245/35R18 92W | XL | | | 627 | 8-9.5 |
| 255/35R18 94W | XL | | 636 | 8.5-10 | |
| | 265/35R18 97W | | XL | 641 | 9-10.5 |
| 40 | 275/35R18 99W | XL | 648 | 9-11 | |
| | | 205/40R18 86W | XL | 622 | 7-8 |
| | 215/40R18 89W | XL | 630 | 7-8.5 | |
| | 225/40R18 92W | XL | 635 | 7.5-9 | |
| | 235/40R18 95W | XL | 644 | 8-9.5 | |
| | 245/40R18 97W | XL | 653 | 8-9.5 | |
| | 255/40R18 99W | XL | 659 | 8.5-10 | |
| 45 | 275/40R18 103W | XL | 677 | 9-11 | |
| | | 215/45R18 93W | XL | 652 | 7-8 |
| | 225/45R18 95W | XL | 659 | 7-8.5 | |
| | 245/45R18 100W | XL | 676 | 7.5-9 | |
| | 255/45R18 99W | | 686 | 8-9.5 | |
| 50 | 225/50R18 99W | XL | 682 | 6-8 | |

| Inch | Series | Dimensions | RF/XL | Overall Diameter (mm) | Approved Rim Width (inch) | |
|---------------|---------------|----------------|---------------|-----------------------|---------------------------|---------|
| 18 | 50 | 235/50R18 97V | | 691 | 6.5-8.5 | |
| | | 235/55R18 100V | | 713 | 6.5-8.5 | |
| 17 | 40 | 195/40R17 81W | XL | 589 | 6.5-7.5 | |
| | | 205/40R17 84W | XL | 595 | 7-8 | |
| | 215/40R17 87W | XL | 602 | 7-8.5 | | |
| | 235/40R17 90W | | 619 | 8-9.5 | | |
| | 45 | 245/40R17 95W | XL | 626 | 8-9.5 | |
| 255/40R17 94W | | | 635 | 8.5-10 | | |
| 195/45R17 85W | | XL | 608 | 6-7.5 | | |
| 50 | 205/45R17 88W | XL | 615 | 6.5-7.5 | | |
| | 215/45R17 91W | XL | 626 | 7-8 | | |
| | 225/45R17 94W | XL | 633 | 7-8.5 | | |
| | 235/45R17 97W | XL | 643 | 7.5-9 | | |
| | 205/50R17 93W | XL | 638 | 5.5-7.5 | | |
| | 215/50R17 95W | XL | 647 | 6-7.5 | | |
| | 225/50R17 98W | XL | 657 | 6-8 | | |
| 55 | 205/55R17 91V | | 657 | 5.5-7.5 | | |
| | | 215/55R17 94W | | 667 | 6-7.5 | |
| | 225/55R17 97W | | 676 | 6-8 | | |
| | 16 | 45 | 195/45R16 84W | XL | 582 | 6-7.5 |
| | | | 205/45R16 87W | XL | 589 | 6.5-7.5 |
| 50 | 215/45R16 90W | XL | 598 | 7-8 | | |
| | 195/50R16 84V | | 600 | 5.5-7 | | |
| | 205/50R16 87V | | 610 | 5.5-7.5 | | |
| | 225/50R16 92W | | 629 | 6-8 | | |
| | 195/55R16 87V | | 618 | 5.5-7 | | |
| 55 | 205/55R16 91W | | 631 | 5.5-7.5 | | |
| | 215/55R16 93W | | 639 | 6-7.5 | | |
| | 225/55R16 95W | | 650 | 6-8 | | |
| | 15 | 50 | 165/50R15 73V | | 548 | 4.5-6 |
| | | | 195/50R15 82V | | 576 | 5.5-7 |
| 55 | 205/50R15 86V | | 583 | 5.5-7.5 | | |
| | 185/55R15 82V | | 583 | 5-6.5 | | |
| | 195/55R15 85V | | 594 | 5.5-7 | | |
| 205/55R15 88V | | 605 | 5.5-7.5 | | | |

XL = Extra Load